



	HIT 8.9 T	HIT 10.11 T	HIT 12.14 T	HIT 16.18 T NEW
	Compare	Compare	Compare	Compare
Working width	8,86 m	11 m	13,2 m	17,2 m
Working width DIN	8,6 m	10,6 m	12,7 m	17 m
Transport width	2,9 m	2,9 m	2,9 m	2,9 m
Transport height	2,7 m	2,7 m	2,7 m	2,7 m
Parking height	2,7 m	2,7 m	2,7 m	2,7 m
Weight	1750 kg	2095 kg	2375 kg	3850 kg
Power requirement	60 hp	75 hp	75 hp	100 hp
Number of rotors	8 pcs.	10 pcs.	12 pcs.	16 pcs.
Number of arms per rotor	6 pcs.	6 pcs.	6 pcs.	6 pcs.
Type of tines	Unequal leg length	Unequal leg length	Unequal leg length	Unequal leg length
Quality of tines	Super C	Super C	Super C	Super C
Tine security system	HEAVY DUTY as standard	HEAVY DUTY as standard	HEAVY DUTY as standard	HEAVY DUTY as standard
Transmission	PTO shaft	PTO shaft	PTO shaft	PTO shaft
Rotor diameter	1,42 m	1,42 m	1,42 m	1,42 m
Wide angle P.T.O.	Wide-angle PTO shaft on one end	Wide-angle PTO shaft on one end	Wide-angle PTO shaft on one end	Wide-angle PTO shaft on one end
Tyres - rotor outside / inside	16 x 6,5-8 / 16 x 9,5-8	16 x 6,5-8 / 16 x 9,5-8	16 x 6,5-8 / 16 x 9,5-8	16 x 6,5-8 / 16 x 9,5-8
Tyres - chassis	260/70-15,3	260/70-15,3	260/70-15,3	380/55-17