

Grass Topper

Super Float Grass Topper

(Standard models)

TOP7SF (2.14m) 7ft Twin Rotor
TOP8SF (2.5m) 8ft Twin Rotor



- Fabricated 3mm one piece deck steel plate fitted on reinforced structural frame along the body of the topper for rigidity.
- Floating top link and hinged body provide bi-lateral movement for constant ground contact and even cut.
- Counter rotation of Twin rotor with Indestructible boron steel blade carriers fitted with free floating boron steel fluted blades.
- Adjustable cutting height 50mm – 200mm
- Converts to working/transport position hydraulically, with spring loaded safety latch when in transport position.
- Hydraulic breakaway standard for the ultimate machine protection and speed of operation. (can be reset from the tractor seat)
- Comer gear boxes with straight drive-line protected by rubber couplings
- PTO over-run and shear bolt protection against rotor impact
- Double jaw support lift arm brackets with Cat 2 lift arm pins.

TOP8SFHD (2.5m) 8ft Twin Rotor (Heavy Duty model) For rushes and heavy grass

- Fitted with 75HP gear box.
- Heavy duty flexible knuckle drive line protected by rubber couplings.
- Fitted with fluted blades with additional straight blades for mulching.



Code	HP	Transport Width	Rotors	Blades	Gearbox	Gearbox Rating	Weight
TOP7SF	70	1.83m	2	4	3	55hp	616kg
TOP8SF	80	1.83m	2	4	3	55hp	650kg
TOP8SFHD	80	1.83m	2	8	3	75hp	670kg