

Muckspreaders

MS 700



- 60 – 100HP requirement.
- Reinforced 4mm body welded inside and out.
- Heavy duty 4 bolt flange bearings mounted away from the body for low maintenance.
- Reinforced drawbar for absolute rigidity when in operation.
- 6 cu. m. capacity (7 cubic yd.)
- Secure simple clip on galvanised chain guard for easy access
- Double starter bars for quick start up.
- 6 ton – 6 stud – 70mm square bolt on axle for safe working operation with 385 x 65R x 22.5 as standard wheels
- Heavy duty balanced rotor with 12mm discharge chains and spreader plates.
- Large wash-out bung
- PTO speed – 540RPM
- Pick up eye and shoe and PTO rest as standard.
- Heavy duty 11/4" (30mm) simplex drive chain
- Heavy Duty galvanised hydraulic opening reinforced lid
- Reinforced loading edge
- Larger wheel option 550 x 45 x 22.5



Code	Cubic Yard Capacity	Power Required	Door	Chain/Flails	Drum Thickness	Overall Length	Width	Loading Height
MS700	6	60hp	HYD	28 no x13mm	4mm	4.7m	2.1m	1.48m

Lights	Brakes	Unladen	PTO Speed	Dia of Drum	Length of Drum	Wheel Sizes Standard	Wheel Sizes Optional
Std	Std	1500kgs	540rpm	140cm	300cm	385x65x22.5	12.5x80x15.3 550x45x22.5