

















WWWALTER WATSON

Greenfield Works, Ballylough Road, Castlewellan, Co. Down, BT31 9JQ, Northern Ireland.

Tel: +44 28 4377 8711 Fax: +44 28 4377 2050


Email: info@walter-watson.co.uk Web: www.walter-watson.co.uk




WWWALTER WATSON

3m Spiral Blade Aerator c/w Rear Hyd Wheel Kit





It Is The Soil That Feeds The Crop While Fertiliser & Manure Feed The Soil




6 Reasons **Why You Should Aerate Your Land**

- 1. It allows oxygen, water & nutrients to get directly to the root system
- 2. It improves root structure and allows fresh roots to grow deeper
- **3.** It improves yields and reduces fertilizer costs
- 4. It improves drainage and slurry absorption resulting in less damage to land
- 5. It allows extended grazing and cutting periods
- **6.** It extends the life of permanent pasture without the need for expensive reseeding.






Ideal Soil Structural Composition



With the use of a large diameter barrel and forward facing 7" tapered Hardox blades we can achieve with a medium size tractor (100hp) the ground speed and aerating process required, with the benefit of fracturing the sub soil up to 30cm (12") deep.

Best results are achieved when the ground is dry, allowing the weight and speed of the Watson aerator to penetrate the hard pan, thus allowing air, water and nutrients directly to the plant roots. This in turn encourages greater root structure, greater nutrient up take and increased grass yield.

Aerator c/w Rear



With the need for increased production from our land today and the unpredictability of our weather, farms everywhere are experiencing soil compaction of one sort or another. At Walter Watsons we have

endeavoured to develop an aerator which gives the farmer of today the opportunity to maximise

production from the farm with a machine which combines strength, weight and speed of operation.

Transport Width – 3.05m

Barrel Diameter – 36"

Barrel Thickness – 20mm

Tapered Hardox Blades

High Quality 2 Pack Paint Finish

■ Double Acting Ram c/w Safety Check Valve

Axle – 3" Solid Shaft (EN8)

Nylon Bush Bearings as Standard

6 Stud Heavy Duty Axle c/w Greasable Pivot Points

40mm Heavy Duty Ring Hitch

LED Lights as Standard

400 x 60 x 15.5 Flotation Wheels

Weight - 2.75 Tonne (Unladen) 4.25 Tonne (Laden)

	Typical Depth	Cause
Surface Pans	0-5cm (0-2")	Traffic (Animal & Machinery)
Grazing Pans	5-10cm (2-4")	Grazing in wet conditions
Machinery Pans	10-15cm (4-6")	Machinery use at wrong time
Ploughing Pans	10-30cm (4-12")	Same depth ploughing





